
563YH


Alloy Steel



Capacity: 500kg-20t / 1Klb-20Klb



Capacity: 100kg-300kg / 100lb-500lb



RoHS

RATED CAPACITY	DIMENSIONS C1	C2	H	H1	L	L1	L2	L3	L4	W	W1	T
lb/inches												
100–500	0.53	0.81	1.25	0.60	5.12	2.25	3.00	1.00	0.62	1.25	1.42	1/2–20 UNF–2B
1,000–4,000; SE5,000	0.53	0.81	1.25	0.60	5.12	2.25	3.00	1.00	0.62	1.25	–	1/2–20 UNF–2B
5,000–10,000	0.78	1.19	1.50	0.75	6.75	3.00	3.75	1.50	0.75	1.50	–	3/4–16 UNF–2B
15,000–20,000	1.03	1.81	2.00	1.00	8.75	4.00	4.75	2.00	1.00	2.00	–	1–14 UNS–2B
kg/mm												
100–300	13.5	20.6	31.8	15.2	130.0	57.2	76.2	25.4	15.8	31.8	36.0	M12X1.75
500–2,000	13.5	20.6	31.8	15.2	130.0	57.2	76.2	25.4	15.8	31.8	–	M12X1.75
2,500; 3,000; 5,000	19.8	30.2	38.1	19.1	171.5	76.2	95.3	38.1	19.1	38.1	–	M18X1.50
10,000	26.2	46.0	50.8	25.4	222.3	101.6	120.7	50.8	25.4	50.8	–	M24X2.00
20,000	30.2	50.0	58.0	32.0	241.5	110.0	132.0	55.0	27.5	58.0	–	M36X2.00

SPECIFICATIONS

Full Scale Output	3.0 mV/V ± 0.25%	**Recommended Excitation**	10V (15V Maximum)
Zero Balance	± 0.02 mV/V	**Insulation Resistance**	>2 [50V DC] GΩ
Non-linearity	< ± 0.017%	**Compensated Temperature Range**	-10°C to 50°C / 14°F to 122°F
Repeatability	< ± 0.017%	**Safe Overload**	150% of full scale
Hysteresis Error	< ± 0.017%	**Breaking Overload**	300% of full scale
Creep in 30 min.	< ± 0.023%	**Seal Type / IP Rating**	Cap.≤300kg/500lb: Environmentally Sealed / IP66
Input Resistance	400Ω ± 20 for kg; 350Ω ± 7 for lb		Cap.≥500kg/1Klb: Environmentally Sealed / IP67
Output Resistance	350Ω ± 3	**Cable Color Code**	Exc+ Red Exc- Black
Element Material	Alloy Steel, Nickel Plated		Sig+ Green Sig- White Shield Bare

PART NUMBER*

Rated Capacity	Part No.	Weight Approx. (kg)
100lb	563YH-100lb	1.0
250lb	563YH-250lb	1.0
500lb	563YH-500lb	1.0
1Klb	563YH-1Klb	1.0
1.5Klb	563YH-1.5Klb	1.0
2Klb	563YH-2Klb	1.0
2.5Klb	563YH-2.5Klb	1.0
LE2.5Klb	563YH-LE2.5Klb	1.7
4Klb	563YH-4Klb	1.0
SE5Klb	563YH-SE5Klb	1.0
5Klb	563YH-5Klb	1.8
10Klb	563YH-10Klb	1.8
15Klb	563YH-15Klb	4.0
20Klb	563YH-20Klb	4.0
100kg	563YH-100kg	1.0
200kg	563YH-200kg	1.0
300kg	563YH-300kg	1.0
500kg	563YH-500kg	1.0
750kg	563YH-750kg	1.0
1t	563YH-1t	1.0
1.5t	563YH-1.5t	1.0
2t	563YH-2t	1.0
2.5t	563YH-2.5t	1.8
3t	563YH-3t	1.8
5t	563YH-5t	1.8
10t	563YH-10t	4.0
20t	563YH-20t	5.6

SE refers to small envelope

* ATEX, FM, IECEx approved versions carry the "-Ex" suffix.

WEIGH MODULE

Model	563YHM2-02	563YHM2-03	563YHM4-02
Page	172	173	170

INTERCHANGEABLE REFERENCE

Brand	Model
Artech	30310
CAS	BSA*
Coti Global	CG-23*
Rice Lake	RL30000*
Rice Lake	RL32018*
Rice Lake	RL35023*
Vishay Celtron	SQB*
Vishay Revere Transducers	5123*
Vishay Sensortronics	65023A*
Vishay Tedea-Huntleigh	3411*

** The dimensions of C2 of interchangeable models are different: 0.53 inch for 100lb to SE5Klb, 0.78 inch for 5Klb and 10Klb, 1.03 inch for 15Klb and 20Klb*

250lb-2.5Klb & 200kg-1t: NTEP 1:5 000 Class III, Single Cell; NTEP 1:9 500 Class III, Multiple Cell

4Klb-20Klb & 2t-5t: NTEP 1:6 000 Class III, Single Cell; NTEP 1:10 000 Class III, Multiple Cell

1.5Klb-5Klb & 500kg-2.5t: OIML MAA C4, Y=15 000; 10Klb-20Klb & 3t-10t: OIML MAA C6, Y=8 500

For further available P/N's & specifications per NTEP/OIML classes, please contact us.

© 2026 ANYLOAD V2 dimensions and specifications subject to change without notice

Product Datasheet Disclaimer

Information Changes:
All product specifications, statements, information, and data (collectively, the "Information") in this catalog or made available elsewhere by ANYLOAD are subject to change. Customers must verify the applicability of the Information at the time of order placement.

Accuracy and Reliability:
While all Information is believed to be accurate and reliable, it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Laboratory Conditions:
Data listed in the datasheet is produced within controlled laboratory settings and may not be reproducible without exact replication of all metrological conditions. Users must validate that a product with the described properties is suitable for their applications.

Interchangeability:
Statements of interchangeability with other manufacturers are based on ANYLOAD's knowledge at the time of publication and are not intended to constitute any warranty concerning the substitutability of an ANYLOAD product with one made by another Manufacturer.

Warranty Voidance:
Any use of the product outside of specifications or any storage or installation inconsistent with product guidance voids any warranty.

Intended Use:
The information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. ANYLOAD provides technical advice without obligation or liability for the advice given or results obtained.

Component Failures:
Although ANYLOAD designs and manufactures its products to stringent quality and safety standards, isolated component failures may still occur. Applications requiring high reliability or safety should employ suitable designs or safeguards to ensure that component failure does not result in personal injury or property damage.

High-Risk Applications:
Unless specifically agreed to in writing, ANYLOAD has not tested or certified its products, services, or deliverables for use in high-risk applications (e.g., medical life support, nuclear facilities, weapon systems). ANYLOAD makes no assurances that the products are suitable for high-risk uses. Under no circumstances does ANYLOAD warrant or guarantee suitability for any customer design or manufacturing process.

Contact authorized ANYLOAD personnel for special terms and conditions regarding products designed for specific safety requirements.

Safety Measures:
All product-related warnings, cautions, and notes must be observed. Customers should not assume that all safety measures are indicated or that other measures may not be required.

California Proposition 65:

⚠ **WARNING:** Some products manufactured or distributed by ANYLOAD may contain trace amounts of chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm. These substances are present in minimal quantities and are typically encapsulated within our products. This warning is provided to enable you to make informed decisions as a consumer.

© 2026 ANYLOAD V1 dimensions and specifications subject to change without notice